

 	GROUP	GAS	PRODUCT INFORMATION	INDEX
	IC		IC-G-B-24-001	D
	POWER RATING			DATE
			11-02-04	
			DEP.	2

<b>GENSET:</b>	<b>SFGLD 240</b>	<b>SPEED:</b>	<b>1500</b>
JACKET WATER TEMPERATURE(°C):	90	<b>FUEL TYPE:</b>	<b>NATURAL GAS</b>
INTERCOOLER WATER TEMP(°C):	55		

APPLICATION:	<b>CONTINUOUS</b>	COMPRESSION RATIO:	<b>11,6:1</b>
COOLING SYSTEM:	<b>TWO CIRCUITS</b>	REGULATION:	<b>Electronic</b>
EXHAUST MANIFOLD TYPE:	WATER COOLED	IGNITION TIMING:	<b>15°</b>
EMISSIONS:		MAX. BACK PRESSURE:	<b>450 mmH2O</b>
	NOX mg/Nm3(8)	AMBIENT CONDITIONS ISO 3046/1:	
	CO mg/Nm3(8)	Atmospheric pressure (kPa)=	<b>100</b>
	NMHC mg/Nm3	Ambient temperature (°C)=	<b>25</b>
		Relative humidity (%)=	<b>30</b>

POWER RATING (4)			NOMINAL	PARTIAL LOADS		
LOAD		%	100%	80%	60%	40%
MECHANICAL POWER	(3, 4, 5)	kWb	<b>419</b>	336	252	168
BMEP		bar	<b>14,0</b>	11,2	8,4	5,6
ELECTRICAL POWER (cosφ 1)		kWe	<b>404,0</b>	323,0	242,0	160,0
ELECTRICAL POWER (cosφ 0,8)		kWe	<b>398,0</b>	319,0	240,0	159,0
FUEL CONSUMPTION	(1)	kW	<b>1053</b>	864	670	485
THERMAL EFFICIENCY		%	<b>39,8</b>	38,9	37,6	34,6
ELECTRICAL EFFICIENCY (cosφ 1)		%	<b>38,4</b>	37,4	36,1	33,0
HEAT IN MAIN WATER CIRCUIT	(1)	kW	<b>265</b>	225	182	141
HEAT IN SECONDARY WATER CIRCUIT	(1)	kW	<b>106</b>	82	58	43
HEAT IN CHARGE COOLER	(1)	kW	<b>60</b>	38	17	6
HEAT IN OIL COOLER	(1)	kW	<b>46</b>	44	41	37
HEAT IN EXHAUST GASES (25 °C)	(1)	kW	<b>242</b>	202	161	118
HEAT IN EXHAUST GASES (120°C)	(1)	kW	<b>176</b>	149	120	89
EXHAUST GAS TEMPERATURE	(1)	°C	<b>376</b>	389	400	410
HEAT TO RADIATION	(1)	kW	<b>21</b>	19	17	15
<b>CARBURETION SETTINGS (2)</b>						
O2 TO EXHAUST(DRY)(ONLY A REFERENCE)		%	<b>9,2</b>	9,1	8,9	8,6

MASS FLOWS					
INTAKE AIR FLOW	(1)	kg/h	<b>2080</b>	1670	1290
EXHAUST GAS FLOW (WET)	(1)	kg/h	<b>2160</b>	1740	1340

<b>NOTES:</b>
1. 100% LOAD TOLERANCES: FUEL CONSUMPTION +5%, COOLING CIRCUIT AND EXHAUST GASES ± 8%, RADIATION ±25% EXHAUST TEMPERATURE ±20°C, MASS FLOWS ± 10%.
2. THE ENGINE PERFORMANCE DATA, TIMING ADVANCE AND CARBURETION SETTINGS ARE VALID FOR A GAS THAT FULFILLS THE REQUIREMENTS DEFINED IN IC-G-D-30-001 AND IC-G-D-30-002
3. NET POWER, MECHANICAL PUMPS NOT INCLUDED.
4. POWERS ARE VALID FOR AMBIENT TEMP. =25°C AND AN ALTITUDE OF =500m. SEE OTHER CONDITIONS IN PI IC-G-B-00-001
5. OVERLOAD NOT ALLOWED
6. THE SPECIFICATIONS AND MATERIALS ARE SUBJECT TO CHANGE WITHOUT NOTIFICATION
7. A ENGINE WITH INLET OR OUTPUT RESTRICTION OVER PUBLISHED LIMITS, OR WITH INADEQUATE MAINTENANCE OR INSTALLATION CAN MODIFY POWER RATING DATA.
8. EMISSIONS ARE CORRECTED TO 5% OF O2.
9. ALTERNATOR VOLTAGE 400 V

CODE3	29.07.2014	Cod.: C-A	Elab:	dis10	Versión: 27.1/09052014	1/1
-------	------------	-----------	-------	-------	------------------------	-----